

Model Rhino Duct Leakage Tester

The Rhino model has been engineered for the most demanding jobs. It includes everything you need to perform a professional duct leakage test. Unit can measure from 9 to 1700 cfm of air leakage (see table below).

Standard Features:

- 230v/1ph/21A (max) operation.
- Simple precision variable speed controller.
- Press RUN and rotate knob to speed up or down.
- 12.5 ft of 8-inch diameter flex-duct (not shown).
- 20 ft of pressure tubing.
- Set of six (1" to 6") orifice plates with +/- 2% error.
- NEW easy to change Twist-Lock orifice plates.
- Certified calibration certificate for each orifice plate.
- Simple to use analog gauges.
- No-flat tires and upper locking casters for horizontal transport and usage.

Options:

- Digital pressure gauges.
- 230v/3ph operation with variable speed controller.
- Low-flow orifice plate for 1 to 10 cfm applications.
- Smoke machine.
- Dust cover.

Compliant with Following Standards:

- EN 1507, Ventilation for Buildings - Sheet Metal Air Ducts with Rectangular Section - Requirements for Strength and Leakage.
- EN 12237, Ventilation for Buildings - Ductwork - Strength and Leakage of Circular Sheet Metal Ducts.
- Eurovent 2/2, Leakage Rate in Sheet Metal Air Distribution Systems.
- DW/143, Ductwork Leakage Testing.
- SMACNA Air Duct Leakage Test Manual.



Tester shown with standard analog gauges

Leakage Capacity of Orifice Plates

Test Pressure (in.wg.)	Recommended Flow Range of Orifice Plate											
	1-inch Plate		2-inch Plate		3-inch Plate		4-inch Plate		5-inch Plate		6.25-inch Plate	
	Min Flow (cfm)	Max Flow (cfm)	Min Flow (cfm)	Max Flow (cfm)	Min Flow (cfm)	Max Flow (cfm)	Min Flow (cfm)	Max Flow (cfm)	Min Flow (cfm)	Max Flow (cfm)	Min Flow (cfm)	Max Flow (cfm)
0.25	9	50	37	200	85	440	160	840	260	1260	455	1700
2	9	45	37	185	85	410	160	785	260	1185	455	1550
4	9	41	37	165	85	375	160	720	260	1100	455	1420
6	9	38	37	155	85	350	160	660	260	1010	455	1330
8	9	35	37	140	85	310	160	590	260	905	455	1185
10	9	30	37	120	85	270	160	515	260	805	455	1035
14	9	19	37	75	85	170	160	325	260	510	455	660
16	9	13	37	55	85	120	160	225	260	365	455	480

Using flex-duct will reduce the capacities listed.